MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PRO-TECH LATEX SEMI-GLUSS

HMIS CODES: H F R P

PRODUCT CODE: 0558-F1

100B

MANUFACTURER'S NAME: O'Leary Paint Company ADDRESS: 415 BAKER ST., LANSING, MI 48910

EMERGENCY PHONE: 800~424-9300 DATE REVISED : 03-03-14

EMERGENCY PHONE: 800-424-9300 INFORMATION PHONE: (517) 482-0473

NAME OF PREPARER : SCOTT BOWER

====== SECTION 11 - MAZARDOUS INGREDIENTS/SARA III INFORMATION ========

		OCCUPAT	IONAL EXPOSURE LIMITS	VAPOR PRESSURE	WEIGHT
HAZARDOUS COMPONENTS	CAS NUMBER	osha pel	ACGIH TLV OTHER	no Hg @ TEMP	PERCENT
+44000007AP=0=000AP4795+844P*P48AAF117F0A************************************					
#ETHYLENE GLYCOL	107-21-1	50 pps	100 mg/m3	0.1 68F	2
TITANILM DIOXIDE	13463 -6 7-7	15 mg/M3	10 mg/M3	N/A	20
HYDROUS KAOLIN CLAY	1332-56-7	15 mg/M3	2 mg/M3	N/A	(5.0%

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

BOILING POINT: 365-374 DEG F VAPOR DENSITY: HEAVIER THAN AIR SPECIFIC GRAVITY (H20=1): 1.3

EVAPORATION RATE: SLOWER THAN ETHER

CDATING V.O.C. : 0.83 LB/GL (99 G/L)

SOLUBILITY IN WATER: INFINITE

APPEARANCE AND ODOR: WHITE OPAQUE LIQUID & SLIGHTLY SWEET DOOR.

FLASH POINT: NA

METHOD USED: NA

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 3.2% UPPER: 15.3%

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELFCONTAINED BREATHING APPARATUS. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFFERABLE. WATER SHOULD BE USED TO COOL CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DUE TO PRESSURE BUILD-UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE. DURING EMERGENCY CONDITIONS, OVEREXPO-SURE TO DECOMPOSITION MAY COUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY SPEARENT. DETAIN MEDICAL ATTENTION. 0558-P1

MATERIAL SAFETY DATA SHEET

PAGE 2 OF 3

STABILITY: STABLE CONDITIONS TO AVOID KEEP FROM FREEZING.

INCOMPATIBILITY (MATERIALS TO AVOID) N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
MAY CAUSE HAZARDOUS FUMES WHEN MEATED TO DECOMPOSITION.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA ------

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT; HEADACHES, NAUSEA, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE MAY CAUSE SKIN AND EYE IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE DRYNESS, ITCHING, CRACKING, BURNING, REDNESS, AND SWELLING ARE ASSOCIATED WITH EXCESSIVE SKIN CONTACT.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE CAN CAUSE GASTRONINTESTINAL IRRITATION. NAUSEA. VOMITING. AND DIARREA.

HEALTH HAZARDS (ACUTE AND CHRONIC)

CARCINOGENICITY: NTP? NO 14AC MONOGRAPHS? NO OSHA REGULATED? NO N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE N/A

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. EYES: IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SKIN: REMOVE WITH SOAP AND WATER, REMOVE SOLLED CLOTHING. INGESTION: DRINK 1 OR 2 GLASSES OF WATER 10 DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSCIAN IMMEDIATELY. HAVE MATERIAL SAFETY DATA SHEET INFORMATION AVAILABLE.

PAGE 3 OF 3

----- SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL 19 RELEASED OR SPILLED PROVIDE MXIMUM VENTILATION. REMOVE ALL SQURCES OF IGNITION. TAKE UP SPILLED MATERIAL WITH SAWDUST, VERMICULITE, OR OTHER ABSORBENT MATERIAL AND PLACE INTO CONTAINERS FOR PROPER DISPOSAL. WASH WITH WATER.

WASTE DISPOSAL METHOD

WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIORMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS SHOULD BE RECYCLED OR DISPOSE OF THROUGH AN APPROVED MANAGEMENT FACILITY.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING STORE BELOW 110F. KEEP FROM FREEZING. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

OTHER PRECAUTIONS KEEP OUT OF REACH OF CHILDREN.

RESPIRATORY PROTECTION

DD NOT BREATHE SPRAY MIST, OR SANDING DUST. WHEN USED IN RESTICTED VENTILATION AREAS, WEAR NIGSH/MSHA APPROVED AIR SUP-PLY RESPIRATOR OR HOOD.

VENTILATION

USE HITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINANT CONCENTRATION BELOW CURRENT APPLICABLE SAFETY STANDARDS IN APPLICATION AND CURING AREAS.

PROTECTIVE GLOVES

GLOVES CONSTRUCTED OF: POLYVINYL ALCHOL, NEOPRENE RUBBER, OR LATEX RUBBER.

EYE PROTECTION

DO NOT GET IN EYES. SAFETY EYE WEAR WITH SPLASH GUARDS OR SIDESHIELD IS RECOMMEND TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT NOT REQUIRED.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SDILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.

D1SCLAIMER

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED BY O'LEARY PAINT CO. TO BE ACCURATE, BUT WE DO NOT ASSUME ANY LIABILITY FOR THE ACCURACY OF THIS INFORMATION. WE NEITHER SUGGEST NOR GUARANTEE THAT ANY HAZARDS MENTIONED ARE THE ONLY ONES WHICH EXIST.