

Revision Date: April 30, 2018

# **Safety Data Sheet**

Revision Date: April 30, 2018 Revision Number: #2

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name Product** Gesso Canvas Primer

Code Product Class 1303G

**Color** Water Thinned Gesso

Αll

Manufacturer

PROART Emergency Telephone Number(s)
415 Baker Street CHEMTREC 800-424-9300

Lansing MI 48910 www.olearypaint.com

## 2. COMPOSITION INFORMATION ON COMPONENTS

## **Hazardous Components**

Chemical Name	CAS•No	Weight % (max)
Limestone	1317-85-3	25
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-547	1
Titanium dioxide	13463-67-7	5
Calcined Kaolin	92704-41-1	5

## 3. HAZARDS IDENTIFICATION

## **Emergency Overview**

Vapors may be irritating to eyes, nose, throat, and lungs. May cause skin irritation and/or dermatitis. May cause allergic skin reaction.

Appearance liquid Odor little or no odor

## **Potential Health Effects**

1303 Gesso Canvas Primer Revision Date: April 30, 2018

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Effects** 

Eyes May cause slight irritation.

Skin May cause skin irritation and/or dermatitis. May cause allergic skin reaction.

Inhalation May cause irritation of respiratory tract.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Effects Repeated contact may cause allergic reactions in very susceptible persons.

See Section 11 for additional Toxicological information.

#### Aggravated Medical Conditions None Known

#### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- 5 Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling Instructions.

Note: The PPE Ming has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

## 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: Do not induce vomiting. Get medical attention immediately.

Notes To Physician Treat symptomatically

#### 5. FIRE MEASURES

Flammability of the product In a fire or if heated, a pressure increase will occur and the container may burst

Extinguishing media

Suitable Use an extinguishing agent suitable for the surrounding fire.

Not suitable Non known.

Special exposure hazards Promptly isolate the scene by removing all persons from the vicinity of the

incident if there is a fire. No action shall be taken involving any personal risk or

without suitable training.

Hazardous combustion products Decomposition products may include the following materials:

carbon oxides metal oxide/oxides

Special protective equipment

for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode

#### 6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled:

Comply with all applicable health and environmental regulations. Ventilate area. Evacuate all unnecessary personnel. Place collected material in proper container. Spilled material is extremely slippery. Complete personal protective equipment must be used during cleanup. Large spills - shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage vessels. Use absorbent to pick up excess residue. Keep salvageable materiel and rinse water out of sewers and water courses. Small spills - use absorbent to pick up residue and dispose of properly.

#### 7. HANDLING AND STORAGE

#### **STORAGE CATEGORY**

Not Applicable

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

## 8. EXPOSRE CONTROLS / PERSONAL PROTECTION

#### **Hazardous Components**

Chemical Name	ACGIH	OSHA	
Limestone	N/E	15 mg/m³ – TWA total 5 mg/m³ – TWA	
Distillates (petroleum), solvent- dewaxed heavy paraffinic	N/E	N/E	
Titanium dioxide	10 mg/m³ – TWA	15 mg/m³ – TWA	
Calcined kaolin	2 mg/m³ – TWA	15 mg/m³ – TWA	

#### Legend

ACGIH – American Conference of Governmental Industrial Hygienists Exposure Limits OSHA – Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment** 

Eye/Face Protection Safety glasses with side-shields.

Skin Protection Protective gloves and impervious clothing.

Respiratory Protection In case of insufficient ventilation wear suitable respiratory equipment.

**Hygiene Measure's** Avoid contact with skin, eyes and clothing. Remove and wash

contaminated clothing before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Not applicable

Not applicable

**Appearance** liquid Odor little or no odor Density (Ibs/gal) 10.0 - 11.0Specific Gravity 1.20 - 1.33Ηα Not available **Evaporation Rate** Not available Vapor Pressure Not available **Vapor Density** Not available 45 - 50 Wt. % Solids Vol. % Solids 30 - 35 Wt. % Volatiles 50 - 55 65 - 70 Vol. % Volatiles 34 VOC (g/L) Boiling Point (°F) 212 Boiling Point (°C) 100 32 Freezing Point (°F) Freezing Point (°C) Not applicable Flash Point (°F) Not applicable Flash Point (°C) Flash Point Method Not applicable

Upper Explosion Limit Lower Explosion Limit

## 10. PHYSICAL AND CHEMICAL PROPERTIES

Stability Stable under recommended storage and handling conditions (see Section 7).

Conditions to avoid No specific data.

Materials to avoid Reactive or incompatible with the following materials: acids, oxidizing materials,

strong alkalis

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Hazardous polymerization Under normal conditions of storage and use, hazardous polymerization will not occur.

#### 11. TOXICOLOGICAL INFORMATION

#### **Acute Toxicity**

Product

No information available

#### Component

<u>Limestone</u>

LD50 Oral: 6,450 mg/kg (Rat) vendor data Sensitization: No sensitizing effects known.

## **Chronic Toxicity**

## Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	ACGIH	IARC	NTP	OSHA Carcinogen
Distillates (petroleum), solvent-	1 – Human			
dewaxed heavy paraffinic	Carcinogen			
Titanium dioxide		2B – Possible		
		Human		

Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint".

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

#### 1303 Gesso Canvas Primer

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity Effects**

#### **Product**

## **Acute Toxicity to Fish**

No information available

## **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No Information available

## 13. DISPOSAL CONSIDERATIONS

#### WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Revision Date: April 30, 2018

## 14. DISPOSAL CONSIDERATIONS

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

## 15. REGULATORY INFORMATION

## **International Inventories**

**United States TSCA** Yes – All components are listed or exempt.

#### **Federal Regulations**

#### SARA 313/312 hazardous categorization

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

This product may contain trace amounts of (other) SARA reportable chemicals. Contact the preparer for further Information.

Revision Date: April 30, 2018

## Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

#### **State Regulations**

#### **California Proposition 65**

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Louisiana	Rhode Island
Limestone	x	X	x		X
Titanium dioxide	Х	Х	Х		Х
Calcined kaolin	X		X		Х

# 16. OTHER INFORMATION

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS; SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to <a href="https://www.epa.gov/lead">www.epa.gov/lead</a>.

**Disclaimer:** The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This Information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent

1303 Gesso Canvas Primer

determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be In accordance with applicable federal, provincial, and local laws and regulations.

Revision Date: April 30, 2018

## **End of MSDS**