



Vintage Acrylic  
Flat  
1850 Series

| Type   | Sheen | Spread Rate   | Recommended Application    | Thinner        | Clean Up               | DRY TIME  |            |                |
|--|-------|---|----------------------------|----------------|------------------------|-----------|------------|----------------|
|  |       |   |                            |                |                        | Tack Free | Re-coat    | Cure           |
| Acrylic/<br>Vinyl<br>Acrylic                           | Flat  | Up to<br>400 - 450<br>Sq Ft<br>Per<br>Gallon  | Brush, Roller,<br>or Spray | Clean<br>Water | Warm<br>Soapy<br>Water | 1 Hour    | 4<br>Hours | 7 - 10<br>Days |
| <b>PRODUCT NAME:</b><br>Vintage Flat<br>Acrylic Enamel |       | Vintage Flat is a premium quality self-priming washable interior flat finish. Vintage Flat dries to a beautiful smooth finish that helps hide minor surface imperfections. Vintage is spatter resistant has very good hide, superior washability and excellent touch-up.  |                            |                |                        |           |            |                |
| <b>WHERE TO USE:</b>                                   |       | Recommended for interior walls and ceilings where a washable finish is required. Ideal for use on properly prepared drywall, plaster, masonry, wood and metal surfaces.   |                            |                |                        |           |            |                |
| <b>Surface Preparation:</b>                            |       | <p><b>New Work:</b> The surface to be coated must be clean and free of oil, grease, rust and other contaminants that could interfere with adhesion.</p> <p><b>Priming –</b><br/>           Drywall &amp; Concrete – Self Priming or use Pro Prime 4190 Drywall Primer<br/>           Wood – Block-It 50 Int/Ext Stain Blocking Primer or Alkyd Undercoat 37-11<br/>           Plaster – Block-It 50 Int/Ext Stain Blocking Primer</p> <p><b>Repaint:</b> The surface to be painted must be clean and free of dirt, chalk, mildew, wax, grease, rust stains or loose flaking paint. Remove loose or flaking paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with this product or the appropriate primer.</p> <p><b>When using Vintage as primer/finish at least two coats are required.</b></p> |                            |                |                        |           |            |                |
| <b>Application:</b>                                    |       | <p>Stir thoroughly with a circular, lifting motion to assure even pigment dispersion.</p> <p>Roller – Use a 3/8" to 1/2" roller cover.<br/>           Brush – Use a nylon / polyester brush.<br/>           Spray – May be applied by spray &amp; back-roll using airless equipment.</p> <p>For best results, use quality applicator tools. Do not sacrifice good results by using inexpensive tools. Apply only when surface and air temperatures are between 50°F and 90°F.</p>   |                            |                |                        |           |            |                |
| <b>NOTE: Formulated without mercury or lead.</b>       |       |   |                            |                |                        |           |            |                |

|                                    |  |
|------------------------------------|--|
| <b>Resin Type:</b>                 | Acrylic / Vinyl Acrylic  |
| <b>Solids:</b>                     | Volume Solids: 36  |
| <b>Weight Per Gallon:</b>          | 10.87 lbs. per gallon  |
| <b>Viscosity:</b>                  | 100 – 104 (Krebs Units)  |
| <b>Specular Gloss:</b>             | 2.0 – 4.0% @ 60°<br>2.0 – 4.0% @ 85°   |
| <b>Recommended Film Thickness:</b> | Wet – 3.5 to 4.0 mils<br>Dry – 1.25 to 1.45 mils   |
| <b>Spread Rate:</b>                | 400 – 450 sq. ft. per gallon.  |
| <b>VOC – VOS Statement:</b>        | This product contains a maximum of 100 grams of VOC/VOS per liter of coating (.83 lbs. per gallon)                             |
| <b>Cautions:</b>                   | <b>CAUTION!</b><br><b>Do not take internally. Close container after each use.</b><br><br><b>KEEP OUT OF REACH OF CHILDREN.</b> |

06/18

