

SECTION NO. 4 ADS 508

[illegible]

ResinType:	Vinyl Toluene Linseed Oil Copolymer
Solids:	Weight – 37.9% Volume – 34.0%
Weight Per Gallon:	6.74 lbs.
Viscosity:	25 – 30 seconds (No. 4 Ford Cup)
Specular Gloss:	70 - 75°F @ 60 degrees
Recommended Film Thickness:	Wet – 3.0 - 3.5 mils Dry - 1.0 - 1.2 mils
VOC – VOS Statement:	This product contains a maximum of 3.75 lbs. or 450 GPL per gallon.
Cautions:	WARNING ! FLAMMABLE ! Contains Petroleum Distillates Keep away from heat & flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin. Use with adequate ventilation. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain & nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. KEEP OUT OF REACH OF CHILDREN.