

ATHLETIC FIELD MARKING PAINT 944 – 2

Section No. 12 ADS - 1305

		Om see al			2 1	DRY TIME			
Туре	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	Tack Free	Re-coat	Cure	
Vinyl Acrylic	Flat	Up to 350 Sq Ft Per Gallon	Airless Spray	Water	Warm Soapy Water	30 Minutes	1 Hour	24 Hours	
PRODUCT NAME: 944 – 2 ATHLETIC FIELD MARKING PAINT		A vinyl acrylic latex coating formulated for machine application to athletic field surfaces. Formulated for stripping and marking natural surfaces; such as grass, cinder and dirt playing fields.							
WHERE TO USE:		For line striping or marking of natural grass; baseball, soccer, football, field hockey and any other field or surfaces. A safe alternative to lime. The product will not harm eyes or grass. Lines will not blue with rough use.							
Surface Preparation:		Apply after grass has been recently cut and avoid morning dew. Do not apply at temperatures below 40 degrees F. As these lower temperatures will slow the dry time of the material. Normal Reduction Rate: Thin with water to a consistency suitable for the particular spray equipment.							
Application:		Airless Spray Tip size and atomization pressure will vary with type of equipment, viscosity and temperature. An orifice of .015021 will provide the most satisfactory spray patterns, dependent upon the surface texture. Best results are more likely obtained by using quality equipment.							
NOTE: Formulated without mercury or lead.									

Resin:	Vinyl Acrylic				
Solids:	Weight – 48.2% Volume – 30.9%				
Weight Per Gallon:	11.23 lbs.				
VOC / VOS Statement:	0.78 Pounds per Gallon 93 Grams per Liter				
Recommended Film Thickness:	N/A Mils wet N/A Mils dry				
Flash Point:	Non Flammable				
Color Availability:	White				
Container Availability:	Five Gallon				
Cautions:	CAUTION! Do not take internally. Close container after each use. KEEP OUT OF REACH OF CHILDREN.				

REV. 06/2011 ADS – 1305

