MATERIAL SAFETY DATA SHEET

PRODUCT NAME: BLOCK-IT ACRYLIC LEED PRIMER HMIS CODES: H F R P
PRODUCT CODE: 10050 1 0 0 B

MANUFACTURER'S NAME: O'Leary Paint Company ADDRESS: 415 BAKER ST., LANSING, MI 48910

EMERGENCY PHONE: 800-424-9300 INFORMATION PHONE: (517) 482-0473
DATE REVISED : 04-15-10 NAME OF PREPARER : SCOTT BOWER

====== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =======

		OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE	WEIGHT
HAZARDOUS COMPONENTS	CAS NUMBER	DSHA PEL	ACGIH TLV OTHER	as Hg & TEMP	PERCENT
*ETHYLENE GLYCOL	107-21-1	56 pps	100 mg/m3	0.1 68F	5
TITANIUM DIDXIDE	13463-67-7	15 mg/M3	10 mg/M3	N/A	15
CALCINED KADLIN	66402-68-4	15 mg/M3	2 mg/M3	N/A	5

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

======= SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =========

BOILING POINT: 365-374 DEG F SPECIFIC GRAVITY (H2O=1): 1.3
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER

COATING V.O.C. : 0.82 LB/GL (99 G/L)

SOLUBILITY IN WATER: INFINITE

APPEARANCE AND ODDR: WHITE OPAQUE LIQUID & SLIGHTLY SWEET ODDR.

======== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =========

FLASH POINT: NA

METHOD USED: NA

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 3.2% UPPER: 15.3%

EXTINGUISHING MEDIA: FDAM, CO2, DRY CHEMICAL, WATER FDG .

SPECIAL FIREFIGHTING PROCEDURES

SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELFCONTAINED BREATHING APPARATUS. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFFERABLE. WATER SHOULD BE USED TO COOL CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DUE TO PRESSURE BUILD-UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE. DURING EMERGENCY CONDITIONS, OVEREXPO-SURE TO DECOMPOSITION MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION. STABILITY: STABLE CONDITIONS TO AVOID KEEP FROM FREEZING.

INCOMPATIBILITY (MATERIALS TO AVOID)
N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION,

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT; HEADACHES, NAUSER, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE MAY CAUSE SKIN AND EYE IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
DRYNESS, ITCHING, CRACKING, BURNING, REDNESS, AND SWELLING ARE ASSOCIATED WITH EXCESSIVE SKIN CONTACT.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
CAN CAUSE GASTRONINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARREA.

HEALTH HAZARDS (ACUTE AND CHRONIC) N/A

CARCINDGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE N/A

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. EYES: IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SKIN: REMOVE WITH SOAP AND WATER, REMOVE SCILED CLOTHING. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSCIAN IMMEDIATELY. HAVE MATERIAL SAFETY DATA SHEET INFORMATION AVAILABLE.

======== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ==========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

PROVIDE MXIMUM VENTILATION. REMOVE ALL SOURCES OF IGNITION.TAKE UP SPILLED MATERIAL WITH SANDUST, VERMICULITE, OR OTHER ABSORBENT MATERIAL AND PLACE INTO CONTAINERS FOR PROPER DISPOSAL. WASH WITH WATER.

WASTE DISPOSAL METHOD

WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIORNMENTAL CONTROL REGULATIONS.EMPTY CONTAINERS SHOULD BE RECYCLED OR DISPOSE OF THROUGH AN APPROVED MANAGEMENT FACILITY.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BELOW 110F. KEEP FROM FREEZING. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

OTHER PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

RESPIRATORY PROTECTION

DO NOT BREATHE SPRAY MIST, OR SANDING DUST. WHEN USED IN RESTICTED VENTILATION AREAS, WEAR NIOSH/MSHA APPROVED AIR SUP-PLY RESPIRATOR OR HOOD.

VENTILATION

USE WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINANT CONCENTRATION BELOW CURRENT APPLICABLE SAFETY STANDARDS IN APPLICATION AND CURING AREAS.

PROTECTIVE GLOVES

GLOVES CONSTRUCTED OF: POLYVINYL ALCHOL, NEOPRENE RUBBER, OR LATEX RUBBER.

EYE PROTECTION

DO NOT GET IN EYES. SAFETY EYE WEAR WITH SPLASH GUARDS OR SIDESHIELD IS RECOMMENDE TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.

DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED BY O'LEARY PAINT CO. TO BE ACCURATE, BUT WE DO NOT ASSUME ANY LIABILITY FOR THE ACCURACY OF THIS INFORMATION. WE NEITHER SUGGEST NOR GUARANTEE THAT ANY HAZARDS MENTIONED ARE THE ONLY DNES WHICH EXIST.