



**WIPING STAIN**  
**Old Masters**  
**11-12000 Series**  
 SECTION NO. 4 ADS-521

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Alkyd	Flat	250-500 Sq. Ft. Per Gallon	Brush, Dipping, Pad or Spray	Mineral Spirits (Not recommended)	Mineral Spirits	4 Hour	8 Hours	7 - 10 Days
<b>PRODUCT NAME:</b> Wiping Stain		<p>Decorator Wood Stain is a thick, rich oil, penetrating, semi-transparent stain for interior or exterior application. It is a pre-mixed wiping stain for better color, control, beauty and richness. It is the ideal stain for the "do-it-yourself" enthusiast and the professional because of its ease in application, consistent results, and forgiveness in use. It is the most efficient stain manufactured to make different surfaces uniform, and is ideal for "refinishing" projects. Its thick, rich formula allows it to be used as a "stain" or "glaze" over any paints, to achieve limitless decorating possibilities. Top coats can be applied in 8 hours.</p>						
<b>WHERE TO USE:</b>		<p>Wood On interior surfaces such as cabinets, furniture, paneling, floors and shelves. On exterior areas such as doors, benches and trim provided it is top coated with an exterior grade varnish.</p>						
<b>Surface Preparation:</b>		<p>The secret to successful application is a properly prepared surface. All surfaces must be sound, dry and free of dust, dirt, wax or grease. Surface defects should be repaired with appropriate patching material.</p>						
<b>Application:</b>		<p>Application on Bare Wood: (used as a stain) Color of stains will vary depending on type and porosity of wood and method of application. Always test stains in a small area for color suitability. Stir thoroughly before and occasionally during application for even distribution of color. Stains may be mixed to achieve special colors. Use stain as is. Do not thin. After cleaning, sand with #120 or #180 sandpaper until smooth. Remove sanding dust. Apply stain liberally with brush, line-free cloth or spray until surface is completely wet. Allow to penetrate for 5 to 15 minutes. Then wipe with a soft cloth, across the grain and then with the grain. If more color is desired, restrain when first coat is dry. If less color is desired, wipe with a cloth dampened with paint thinner. Allow to dry thorough before applying a clear finish, such as our polyurethane.</p>						
<b>NOTE: Formulated without mercury or lead.</b>								

<b>Resin Type:</b>	Alkyd
<b>Solids:</b>	Weight – 35.0% Volume – 24.0%
<b>Weight Per Gallon:</b>	7.6 lbs.
<b>Viscosity:</b>	400-500 cps using Brookfield Viscometer.
<b>Specular Gloss:</b>	1 – 2 % @ 85 degrees
<b>Recommended Film Thickness:</b>	Material is a penetrating finish, no appreciable film build should be achieved.
<b>VOC – VOS Statement:</b>	This product contains less than 2.92 lbs or 350 GPL per gallon.
<b>Cautions:</b>	<p style="text-align: center;"><b>CAUTION! Combustible</b> <b>Contains Petroleum Distillates</b></p> <p>If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. Keep away from heat &amp; flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin. Use with adequate ventilation. <b>NOTICE:</b> Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. <b>KEEP OUT OF REACH OF CHILDREN.</b></p>

