



**SEMI-GLOSS
TRIM VARNISH**

151-100

SECTION NO. 4 ADS 507

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Tall Soya Latex	Satin	400 - 500 Sq Ft Per Gallon	Brush, Roller, or Spray	Mineral Spirits	Mineral Spirits	4 Hours	24 Hours	7 - 10 Days
PRODUCT NAME: SEMI-GLOSS TRIM VARNISH 151-100		This Trim Varnish exhibits exceptional durability and abrasion resistance. It is designed to enhance the natural beauty of wood with either a high gloss or an eggshell sheen.						
WHERE TO USE:		Wood On interior areas such as floors, trim, furniture, doors or cabinets.						
Surface Preparation:		Surface to be coated must be clean and free of dust, grease, dirt or wax. If wax is a suspect contaminant, remove with a commercial wax stripper. New interior wood must be sanded smooth and sealed with 390 Sanding Sealer, allowed 4 – 6 hours dry time, sanded lightly and top-coated with 151-100. Additional coats of this trim varnish may be applied after 24 hours to achieve a deep, rich appearance. Sand lightly between coats with fine sandpaper.						
Application:		This Trim Varnish may be brushed, rolled or sprayed. Best rolling results are obtained with a short nap mohair roller. For best brush application, use a china bristle brush. When brushing or rolling, flow material on with a minimum of strokes. Thinning is not recommended, if necessary, use mineral spirits sparingly. Do not apply when surface or air temperatures are below 40°F. Not for exterior or marine use.						
NOTE: Formulated without mercury or lead.								

Resin:	Tall Soya Alkyd
Solids:	Weight – 34.9% Volume – 23.9%
Weight Per Gallon:	7.44 lbs.
Viscosity:	57 – 62 (Krebs Units)
Specular Gloss:	22 – 27% @ 60 Degrees
Recommended Film Thickness:	Wet – 3.1 to 3.6 mils Dry - .74 to .86 mils
VOC – VOS Statement:	This product contains less than 3.75 lbs. or 450 GPL per gallon of coating.
Cautions:	<p style="text-align: center;">CAUTION! Combustible! Contains Petroleum Distillates.</p> <p>Keep away from heat and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin. Use with adequate ventilation. NOTICE: Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.</p> <p style="text-align: center;">KEEP OUT OF REACH OF CHILDREN.</p>