

M A T E R I A L   S A F E T Y   D A T A   S H E E T

ACRYLIC LATEX EGGSHELL WB

Page: 1

PRODUCT NAME: ACRYLIC LATEX EGGSHELL WB  
PRODUCT CODE: 1007

HMIS CODES: H F R P  
1 0 0 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: O'Leary Paint Company  
ADDRESS : 415 Baker Street  
PMI Division  
Lansing, MI. 48910

EMERGENCY PHONE : DATE PRINTED : 11/28/01  
INFORMATION PHONE : (517) 487-2033 NAME OF PREPARER : SCOTT BOWER

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

WEIGHT REPORTABLE COMPONENTS PERCENT	CAS NUMBER	mm Hg	TEMP	VAPOR PRESSURE
ETHYLENE GLYCOL	107-21-1	.1	68	5
OSHA PEL: 50 ppm, ACGIH TLV: 100 mg/m3				

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*  
WARNINGS ON CRYSTALLINE SILICA NEED ONLT BE OBSERVED WHEN SANDING OR GRINDING ON DRIED PAINT FILM. WHEN DOING SO A NIOSH /MSHA DUST AND MIST RESPIRATOR SHOULD BE WORN.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 387 deg F                      SPECIFIC GRAVITY (H2O=1): 1.34  
VAPOR DENSITY: HEAVIER THAN AIR              EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 1.81 lb/gl                    MATERIAL V.O.C.: 0.83 lb/gl  
SOLUBILITY IN WATER: INFINITE  
APPEARANCE AND ODOR: WHITE OPAQUE LIQUID & SLIGHTLY SWEET ODOR.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: 232 deg F                      METHOD USED: TCC  
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 3.2              UPPER: 15.3

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES  
SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER SHOULD BE USED TO COOL CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS  
DUE TO PRESSURE BUILD-UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE. DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE  
CONDITIONS TO AVOID  
KEEP FROM FREEZING.

INCOMPATIBILITY (MATERIALS TO AVOID)  
N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS  
MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION.

HAZARDOUS POLYMERIZATION: WILL OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT; HEADACHES, NAUSEA, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
MAY CAUSE SKIN AND EYE IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
DRYNESS, ITCHING, CRACKING, BURNING, REDNESS, AND SWELLING ARE ASSOCIATED WITH  
EXCESSIVE SKIN CONTACT.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

HEALTH HAZARDS (ACUTE AND CHRONIC)  
AVOID LONG TERM AND REPEATED CONTACT. CONTAINS A FORM OF CRYSTALLINE SILICA.  
LONG TERM EXPOSURE TO HIGH LEVELS OF THIS MATERIAL MAY LEAD TO A DISABLING LUNG  
INJURY KNOWN AS SILICOSIS.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No  
CALCIUM CARBONATE CONTAINS CRYSTALLINE SILICA AS A MINOR IMPURITY;IT IS PRESENT  
IN THEORETICAL 1% TO 1.5% LEVELS. CRYSTALLINE SILICA HAS BEEN REVIEWED BY IARC  
AND THEY HAVE FOUND EVIDENCE FOR PULMONARY CARCINOGENICITY IN HUMANS.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE  
N/A

EMERGENCY AND FIRST AID PROCEDURES  
INHALATION:REMOVE TO FRESH AIR. EYES:IN CASE OF EYE CONTACT, FLUSH WITH LARGE  
AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SKIN:REMOVE WITH SOAP AND WATER,  
REMOVE SOILED CLOTHING. INGESTION:DRINK 1 OR 2 GLASSES OF WATER TO DILUTE.DO NOT  
INDUCE VOMITING. CONSULT PHYSICIAN IMMEDIATELY. HAVE MATERIAL SAFETY DATA SHEET  
INFORMATION AVAILABLE.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED  
PROVIDE MAXIMUM VENTILATION. REMOVE ALL SOURCES OF IGNITION.TAKE UP SPILLED  
MATERIAL WITH SAWDUST,VERMICULITE, OR OTHER ABSORBENT MATERIAL AND PLACE INTO  
CONTAINERS FOR PROPER DISPOSAL. WASH WITH WATER.

WASTE DISPOSAL METHOD

WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL  
ENVIRONMENTAL CONTROL REGULATIONS.EMPTY CONTAINERS SHOULD BE RECYCLED OR DISPOSE  
OF THROUGH AN APPROVED MANAGEMENT FACILITY.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BELOW 110F. KEEP FROM FREEZING. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

OTHER PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

DO NOT BREATHE SPRAY MIST, OR SANDING DUST. WHEN USED IN RESTRICTED VENTILATION  
AREAS, WEAR NIOSH/MSHA APPROVED AIR SUP- PLY RESPIRATOR OR HOOD.

VENTILATION

USE WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST

VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINANT CONCENTRATION BELOW  
CURRENT APPLICABLE SAFETY STANDARDS IN APPLICATION AND CURING AREAS.

PROTECTIVE GLOVES

GLOVES CONSTRUCTED OF:POLYVINYL ALCOHOL, NEOPRENE RUBBER, OR LATEX RUBBER.

EYE PROTECTION

DO NOT GET IN EYES. SAFETY EYE WEAR WITH SPLASH GUARDS OR SIDESHIELD IS  
RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING  
OR USING THE WASHROOM.

===== SECTION IX - DISCLAIMER =====

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED BY O'LEARY PAINT CO.  
TO BE ACCURATE, BUT WE DO NOT ASSUME ANY LIABILITY FOR THE ACCURACY OF THIS  
INFORMATION. WE NEITHER SUGGEST NOR GUARANTEE THAT ANY HAZARDS MENTIONED ARE THE  
ONLY ONES WHICH EXIST.