

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: LATEX SEMI-GLOSS  
PRODUCT CODE: 2902

HMS CODES: H F R P  
1 0 0 B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: O'Leary Paint Company  
ADDRESS: 415 BAKER ST., LANSING, MI 48910  
EMERGENCY PHONE: 800-424-9300 INFORMATION PHONE: (517) 482-0473  
DATE REVISED : 05-17-01 NAME OF PREPARER : SCOTT BOWER

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
		OSHA PEL	ACGIH TLV	OTHER		
*ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	25 ppm	20 ppm		0.7 68F	2
*METHANOL / METHYL ALCOHOL	67-56-1	200ppm	200ppm		21.7 68F	4

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 365-374 DEG F SPECIFIC GRAVITY (H2O=1): 1.2  
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C. : 1.53 LB/GL ( 183 G/L)  
SOLUBILITY IN WATER: INFINITE  
APPEARANCE AND ODOR: WHITE OPAQUE LIQUID & SLIGHTLY SWEET ODOR.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: NA METHOD USED: NA  
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 6.0% UPPER: 36.0%

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

FIREFIGHTING PROCEDURES

PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELFCONTAINED BREATHING APPARATUS. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERRED. WATER SHOULD BE USED TO COOL CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DUE TO PRESSURE BUILD-UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE. DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

## ===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE  
CONDITIONS TO AVOID  
KEEP FROM FREEZING.

INCOMPATIBILITY (MATERIALS TO AVOID)  
N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS  
MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
N/A

## ===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT; HEADACHES, NAUSEA, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
MAY CAUSE SKIN AND EYE IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
DRYNESS, ITCHING, CRACKING, BURNING, REDNESS, AND SWELLING ARE ASSOCIATED WITH EXCESSIVE SKIN CONTACT.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

HEALTH HAZARDS (ACUTE AND CHRONIC)  
N/A

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO  
N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE  
N/A

EMERGENCY AND FIRST AID PROCEDURES  
INHALATION: REMOVE TO FRESH AIR. EYES: IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES.  
SKIN: REMOVE WITH SOAP AND WATER, REMOVE SOILED CLOTHING. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE  
VOMITING. CONSULT PHYSICIAN IMMEDIATELY. HAVE MATERIAL SAFETY DATA SHEET INFORMATION AVAILABLE.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

PROVIDE MAXIMUM VENTILATION. REMOVE ALL SOURCES OF IGNITION. TAKE UP SPILLED MATERIAL WITH SAWDUST, VERMICULITE, OR OTHER ABSORBENT MATERIAL AND PLACE INTO CONTAINERS FOR PROPER DISPOSAL. WASH WITH WATER.

## WASTE DISPOSAL METHOD

WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS SHOULD BE RECYCLED OR DISPOSED OF THROUGH AN APPROVED MANAGEMENT FACILITY.

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BELOW 110°F. KEEP FROM FREEZING. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

## OTHER PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

## ===== SECTION VIII - CONTROL MEASURES =====

## RESPIRATORY PROTECTION

DO NOT BREATHE SPRAY MIST, OR SANDING DUST. WHEN USED IN RESTRICTED VENTILATION AREAS, WEAR NIOSH/MSHA APPROVED AIR SUPPLY RESPIRATOR OR HOOD.

## VENTILATION

USE WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINANT CONCENTRATION BELOW CURRENT APPLICABLE SAFETY STANDARDS IN APPLICATION AND CURING AREAS.

## PROTECTIVE GLOVES

GLOVES CONSTRUCTED OF: POLYVINYL ALCOHOL, NEOPRENE RUBBER, OR LATEX RUBBER.

## EYE PROTECTION

DO NOT GET IN EYES. SAFETY EYE WEAR WITH SPLASH GUARDS OR SIDESHIELD IS RECOMMENDED TO PREVENT CONTACT.

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED.

## WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.

## ===== SECTION IX - DISCLAIMER =====

## DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED BY O'LEARY PAINT CO. TO BE ACCURATE, BUT WE DO NOT ASSUME ANY LIABILITY FOR THE ACCURACY OF THIS INFORMATION. WE NEITHER SUGGEST NOR GUARANTEE THAT ANY HAZARDS MENTIONED ARE THE ONLY ONES WHICH EXIST.