



BLOCK IT
ACRYLIC PRIMER/SEALER

50

SECTION NO. 3 ADS 450

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Acrylic	Flat	Up to 400 Sq Ft Per Gallon	Brush, Roller, or Spray	Clean Water	Warm Soapy Water	30 Minutes	1 Hour	7 Days
PRODUCT NAME: 50 BLOCK IT Acrylic Primer / Sealer		A high hiding, fast drying low odor acrylic primer sealer that is easy to apply to both new and old, interior and exterior surfaces. Resists burning from hot or green plaster, and it lays the nap well on paper surfaced drywall construction. It's fast drying makes it possible to apply two coats in one day. Provides an excellent foundation for all paints, seals stains of various types: asphalt, smoke, light water stains, perspiration and wood stains (except redwood and cedar).						
WHERE TO USE:		Wood Plaster Drywall Acoustical Tile Brick Concrete	On drywall construction, over joint cement, interior plaster, wood, brick, concrete, building blocks, masonite, and asphalt impregnated surfaces. It is an excellent first coat sealer on insulation material of asbestos used as pipe covering. May also be used as an undercoat over flat surfaces where it is desired to apply a coat of alkyd or oil base enamel without danger of gloss strike in. May be applied directly to enameled, varnished and galvanized surfaces. This primer is not formulated for use as the original primer applied at the factory to industrial or consumer products. (O.E.M.)					
Surface Preparation:		Surface to be painted must be clean and free of dirt, chalk, wax, grease, rust, or loose, flaking paint. Dirt and chalk should be removed by scrubbing with warm soapy water, and thoroughly rinsed with clean water. Wax should be removed with a commercial wax stripper, or by solvent cleaning. Grease should be cleaned by using Coronado Sur-Prep 1. Rust must be removed by hand sanding vigorously, or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application.						
Application:		May be applied by brush, roller or spray, airless or conventional. Apply one coat of #50 Block-It Acrylic Primer Sealer as it comes from the container over the entire surface. Apply generously, brushing from the dry area into the already painted surface. Do not apply when air or surface temperatures are below 50°F. May be thinned sparingly with water not to exceed ½ pint per gallon.						
NOTE: Formulated without mercury or lead.								

Resin:	Acrylic
Solids:	Weight – 51.6% Volume – 34.3%
Weight Per Gallon:	10.9 lbs.
Viscosity:	90 – 95 (Krebs Units)
Specular Gloss:	6 – 10% @ 60 Degrees
Recommended Film Thickness:	Wet – 3.5 to 4.0 mils Dry - 1.0 to 1.2 mils
VOC – VOS Statement:	This product contains less than 2.9 lbs. or 350 GPL per gallon of coating.
Cautions:	<p>CAUTION! Do not take internally. Close container after each use.</p> <p>KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING !</p>