



## ACRYLIC TRAFFIC PAINT

### 66 LINE

6601 – White  
 6602 – Black  
 6656 – Yellow

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Vinyl Acetate Acrylic	Flat	3" line / 400' 4" line / 300' 5" line / 240' 6" line / 200'	Brush, Roller, Pad or Spray	Clean Water	Warm Soapy Water	30 Minutes	4 Hours	7 Days
<b>Product Name :</b> 66 LINE Acrylic Traffic Paint		A fast drying paint for marking traffic lanes on streets, highways, parking lots, warehouses and other areas where such marking is required. Traffic beads may be dropped into this coating while wet to provide reflectorized markings. If beads are applied, they should be broadcast into the wet paint at a rate of 6 lbs. of beads per gallon of paint.						
<b>WHERE TO USE:</b>		Concrete Asphalt	On interior or exterior horizontal surfaces such as streets, highways, parking lots or warehouses.					
<b>Surface Preparation:</b>		Surface to be marked must be clean, free of dust, oil, grease, wax, rust or bleeding stains. Any asphaltic seal coat applied to the surface prior to application of this traffic paint should be dry for at least 48 hours before this traffic paint is used. Existing traffic lines can be obliterated on asphalt surfaces by coating with 6602 Black Traffic Paint prior to application of the required color.						
<b>Application:</b>		May be applied by brush, roller, spray, hand or automatic line markers. Do not apply when air or surface temperatures are below 50°F. Do not apply to extremely hot surfaces. Stir contents thoroughly from the bottom before using. Paint only in dry weather. Thinning is not normally required, if necessary, thin sparingly with clean water. This Acrylic Traffic Paint will dry to no pickup (ASTM D-711) in 30 minutes at 70° to 80°F. Acrylic Traffic Paint is not designed as an anti-slip coating. If skid resistance is important, apply Coronado Step-Safer.						

<b>Resin Type:</b>	Vinyl Acetate / Acrylic												
<b>Solids:</b>	<table border="1"> <thead> <tr> <th></th> <th><b>6601</b></th> <th><b>6602</b></th> <th><b>6656</b></th> </tr> </thead> <tbody> <tr> <td><b>Weight</b></td> <td>68.9%</td> <td>61.8%</td> <td>62.3%</td> </tr> <tr> <td><b>Volume</b></td> <td>50.5%</td> <td>44.9%</td> <td>44.6%</td> </tr> </tbody> </table>		<b>6601</b>	<b>6602</b>	<b>6656</b>	<b>Weight</b>	68.9%	61.8%	62.3%	<b>Volume</b>	50.5%	44.9%	44.6%
	<b>6601</b>	<b>6602</b>	<b>6656</b>										
<b>Weight</b>	68.9%	61.8%	62.3%										
<b>Volume</b>	50.5%	44.9%	44.6%										
<b>Weight Per Gallon:</b>	<table border="1"> <thead> <tr> <th></th> <th><b>6601</b></th> <th><b>6602</b></th> <th><b>6656</b></th> </tr> </thead> <tbody> <tr> <td><b>lbs / gallon</b></td> <td>13.02 lbs/gal</td> <td>11.82 lbs/gal</td> <td>11.96 lbs/gal</td> </tr> </tbody> </table>		<b>6601</b>	<b>6602</b>	<b>6656</b>	<b>lbs / gallon</b>	13.02 lbs/gal	11.82 lbs/gal	11.96 lbs/gal				
	<b>6601</b>	<b>6602</b>	<b>6656</b>										
<b>lbs / gallon</b>	13.02 lbs/gal	11.82 lbs/gal	11.96 lbs/gal										
<b>Viscosity:</b>	80 – 85 (Krebs Units)												
<b>Flash Point:</b>	200°F. (TT-P-141, Method 4293)												
<b>Specular Gloss:</b>	2 – 3% @ 85 degrees												
<b>Sag Rating:</b>	N/A												
<b>Recommended Film Thickness:</b>	Wet - 12.0 to 15.0 mils Dry - 3.4 to 4.2 mils												
<b>Light Reflectance:</b>	90% (White)												
<b>Cautions:</b>	<p style="text-align: center;"><b>6601, 6602, 6656</b> <b>CAUTION!</b> Do not take internally. Close container after each use. <b>KEEP OUT OF REACH OF CHILDREN</b> <b>KEEP FROM FREEZING</b></p> <p style="text-align: center;"><b>CAUTIONS</b> CONTAINS LEAD DRIED FILM OF THIS PAINT MAY BE HARMFUL IF EATEN OR CHEWED Do not apply on toys and other children's articles, furniture, or interior surfaces of any dwelling or facility which may be occupied or used by children. Do not apply on those exterior surfaces of dwelling units, such as windowsills, porches, stairs or railings, to which children may be commonly exposed.</p> <p style="text-align: center;"><b>Use only with adequate ventilation.</b> <b>KEEP OUT OF REACH OF CHILDREN.</b></p>												
<b>VOC / VOS Statement:</b>	This product contains a maximum of 0.83 lbs. VOC/VOS per gallon of coating.												

