



**PRO HIDE**  
**Latex / Eggshell Finish**  
**7200 LINE**

SECTION NO. 2 ADS - 356

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Vinyl Acrylic	Eggshell Enamel	Up to 400 Sq Ft Per Gallon	Brush, Roller, Pad or Airless Spray	Clean Water	Warm Soapy Water	60 Minutes	4 Hours	7 Days
<b>PRODUCT NAME:</b> 7200 LINE PRO HIDE LATEX / EGGSHELL ENAMEL		Pro Hide Eggshell Enamel is designed to be applied with equal success by contractors or do-it-yourselfers. It applies easily without spattering, covers most surfaces in one coat and may be washed repeatedly without film damage. Perfect for children's bedrooms, hallways or wherever a low sheen is desirable. This product complies with LEED Green Building Rating System GS-11 for interior non-flat paints.						
<b>WHERE TO USE:</b>		Drywall Plaster Wood Metal Masonry	Pro Hide Latex Eggshell can be applied to walls, woodwork, trim, paneling, doors or dadoes. It is a good choice for interior bedrooms, family rooms, hallways, recreation rooms, commercial or rental properties.					
<b>SURFACE PREPARATION:</b>		<p><b>New Work:</b> The surface to be coated must be clean and free of dust, grease, wax, rust, oil, and bleeding stains.</p> <p><b>Priming:</b>            Drywall –For best results use #4190 Latex Primer Sealer or 7190.            Plaster – For best results use #50 Block-Out            Wood – Alkyd Primer Undercoat #37-11            Ferrous Metal – Rust inhibiting metal primer such as #35-111, #925-147.            Galvanized/Non-Ferrous - #36-11 or #180-11.            Masonry – Masonry Sealer #43-10 or #48-11. To fill porous block use #529-11 Latex Block Filler.</p> <p><b>Repaint Work:</b> On previously painted surfaces in good repair, no priming is generally necessary. On glossy surfaces, remove the sheen with sandpaper or steel wool. Patch holes or cracks with appropriate filler. Spot prime bare areas with indicated primer. Remove any oil, chalk, dirt, wax or dust, prior to re-coating. Any loose or flaking paint should be removed and the edges feather sanded to produce a smooth, uniform surface.</p>						
<b>APPLICATION:</b>		Stir product thoroughly with a circular, lifting motion to disperse into a homogenous liquid. Roller – 3/8" to 1-1/4" nap, depending on surface texture. Brush – Nylon or polyester filament. Airless Spray – Tip size at atomization pressure will vary with type of equipment, viscosity and temperature. An orifice of .017 - .019 will provide the most satisfactory spray pattern.  Best results are more likely obtained by using quality application tools. Do not apply directly over chalky surfaces or bleeding stains.						
<b>NOTE: Formulated without mercury or lead.</b>								

<b>RESIN TYPE:</b>	Vinyl Acrylic
<b>SOLIDS:</b>	Weight – 51.0% Volume – 37.2%
<b>WEIGHT PER GALLON:</b>	10.8 lbs.
<b>VISCOSITY:</b>	102 – 105 (Krebs Units)
<b>SPECULAR GLOSS:</b>	5 – 10% @ 85 Degrees
<b>RECOMMENDED FILM THICKNESS:</b>	Wet – 4.0 to 4.5 mils Dry – 1.7 to 1.9 mils
<b>VOC – VOS STATEMENT:</b>	This product contains 113 grams per liter.
<b>CAUTIONS:</b>	<b>CAUTION!</b> Do not take internally. Close container after each use.  <b>KEEP OUT OF REACH OF CHILDREN.</b>

