



**Pro Prime
High Hide
Interior Latex Primer
1200.00 Line**

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Latex	Flat	350 to 400 Sq Ft Per Gallon	Brush, Roller or Spray	Clean Water	Warm Soapy Water	1 Hour	2 Hours	7 Days
PRODUCT NAME: 1200-00 PRO PRIME High Hide Primer		Pro Prime High Hide interior latex primer that dries quickly and may be applied to drywall, masonry and non-bleeding wood surfaces. Formulated for easy application, Pro Prime High Hide Latex/Primer dries quickly, gives good coverage, seals surface to eliminate flashing to top coat. Quick dry may be sanded or recoated in two hours.						
WHERE TO USE:		Interior Drywall, Masonry, MDF and Non-Bleeding Wood substrates.						
SURFACE PREPARATION:		Stir thoroughly before using. Surface must be clean, dry and free of dirt, grease and grime. Remove all loose and flaking paint. Fill all holes cracks, and surface defects. Sand to a smooth finish. Dull glossy surfaces by sanding. Fill cinder block and rough masonry with O'Leary Acrylic Block Filler. For best coverage primers and block fillers should be tinted to approximate finish color. Concrete must cure at least 30 days before painting. Ph must be 10.0 or lower. For Ph greater than 10.0 use #50 Block It (up to Ph12) or 5090 Primer/Sealer (up to Ph 13).						
LEAD WARNING!		WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS A BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start find out how to protect yourself and your family by contacting the National Lead Information Hotline 1-800-424-LEAD or log on to www.epa.gov/lead .						
APPLICATION:		Stir product with a circular, lifting motion before you begin to paint. May be applied by brush, roller or spray, at a rate of application not to exceed 400 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush results, use a quality synthetic filament brush. For roller application, use a 3/8" nap cover for smooth surfaces, a 1/2" nap cover for semi-rough surfaces and a 3/4" nap cover for rough surfaces. For spray application, may be thinned with clean water, up to 10% reduction if necessary. Satisfactory results are most likely obtained by using quality application tools. Apply when surface temperature is above 50° F.						
NOTE: Formulated without mercury or lead.								

RESIN TYPE:	Vinyl Acetate / Acrylic
SOLIDS:	Weight – 41.0% Volume – 28.3%
WEIGHT PER GALLON:	10.34 lbs.
VISCOSITY:	102 – 106 (Krebs Units)
SPECULAR GLOSS:	4 – 5 @ 85 degrees
RECOMMENDED FILM THICKNESS:	Wet – 4.0 to 4.6 mils Dry – 1.13 to 1.3 mils
VOC – VOS STATEMENT:	This product contains less than 0.84 lbs or 100 GPL per gallon.
CAUTIONS:	CAUTION! Do not take internally. Close container after each use. KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING.

05/04/21

