



**PRO-TECH
ALKYD EGGSHELL
1800 LINE**

SECTION NO. 2 ADS - 303

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Modified Soya Alkyd	Eggshell	Up to 400 Sq Ft Per Gallon	Brush, Roller, Pad or Spray	Mineral Spirits	Mineral Spirits	4 Hours	24 Hours	10 Days
PRODUCT NAME: 1600 LINE Pro-Tech Alkyd Eggshell		Alkyd Eggshell Enamel is designed to produce a soft, semi-lustre finish which is perfect for kitchens, bathrooms, children's bedrooms, trim work. Any area where a durable subdued gloss is desirable. May be washed repeatedly without damaging the film.						
WHERE TO USE:		Drywall Plaster Wood Metal Masonry	On interior walls, trim or cabinets such as in kitchens, bathrooms or children's bedrooms.					
Surface Preparation:		<p>Surface to be painted must be clean and free of dirt, chalk, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by scrubbing with warm soapy water and thoroughly rinsed with clean water. Wax should be removed with a commercial wax stripper or by solvent cleaning. Grease should be cleaned by using Sur-Prep I. Rust must be removed by hand sanding or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with the appropriate primer.</p> <p>Priming - (New or Bare Surfaces) Plaster/Drywall – For best results use O'Leary Primer Sealer 1190 or #50 BlockOut. Wood – Use O'Leary Undercoat 37-11. Masonry – Use Masonry Sealer 43-11 or 48-11. 946-11 Block Filler for porous Block. Ferrous Metal – Use Metal primers 35-111 or 36-11. Non-Ferrous Metal – Use Perma Bond 100-10. Galvanized – Use 36-11 or 180-11.</p>						
Application:		Stir product with a circular, lifting motion before you begin to paint. Alkyd Eggshell Enamel may be applied by brush, roller, pad, or spray techniques, at a rate of application not to exceed 400 sq ft per gallon. Surface texture and porosity will effect actual yield. For best brush application results, use a quality natural hair bristle brush. For roller application, use a ¼" nap cover for smooth surfaces, a 3/8" or ½" nap cover for semi-rough surfaces and a ¾" nap cover for rough surfaces. Thinning is not normally recommended, if required use mineral spirits sparingly. For spray application, Alkyd Eggshell Enamel may be thinned with mineral spirits, up to 10% reduction if necessary. Apply when surface temperature is above 40° F.						
NOTE: Formulated without mercury or lead.								

Resin Type:	Modified Soya Alkyd
Solids:	Weight - 70.4% Volume - 53.5%
Weight Per Gallon:	10.84 lbs.
Viscosity:	74 – 77 (Krebs Units)
Specular Gloss:	10 – 15% @ 60 degrees
Recommended Film Thickness:	Wet – 4.0 to 4.5 mils Dry - 12.1 to 2.4 mils
VOC / VOS Statement:	This product contains less than 3.17 lbs or 250 G.P.L. per gallon.
Cautions:	<p>CAUTION: Combustible Contains Mineral Spirits</p> <p>Keep away from heat & flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin. Use with adequate ventilation. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.</p> <p>KEEP OUT OF REACH OF CHILDREN !</p>