



**RUSTIC OIL STAIN
SEMI - TRANSPARENT**

3541 LINE

SECTION NO. 11 ADS 1200

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Oil	Satin	Up to 250 Sq Ft Per Gallon	Brush, Roller, Pad or Spray	Mineral Spirits	Mineral Spirits	4 - 6 Hours	Over Night	24 Hours
PRODUCT NAME: 3541 Rustic Stain Semi - Transparent		Wood Stain preserves natural wood fibers and repels damaging moisture, providing dimensional stability against swelling and warping, plus offers protection accentuating the natural wood grain and texture.						
WHERE TO USE:		Siding Shakes Shingles Fences	Can be applied to new or unsealed wood surfaces such as smooth or rough sawn siding, decks, shakes, etc. Do not apply to abraded plywood. It is not intended for below grade use or where wood comes into direct contact with the ground. Avoid contact with skin and food products.					
Surface Preparation:		The surface to be stained must be completely clean and dry. Dirt, dust, chalk, or other loose material should be removed by power washing, sanding or wire brushing. If mildew is present, remove it by washing with a solution of one part liquid bleach to three parts water. Rinse thoroughly with clean water. Always wear gloves, eye protection devices and protective clothing when working with bleach.						
Application:		Stir product thoroughly with a circular, lifting motion before and periodically during application. Apply stain liberally with a quality brush, pad or roller. Can be applied by airless or conventional spray. The more stain absorbed by the wood, the greater the protection. Thinning is not recommended, however, if needed use mineral spirits sparingly. Applying stain in direct, hot sunlight should be avoided. Do not apply if rain is threatening. The actual stain color can vary depending on the type, texture, grain or color of the wood. Prepare a test panel to determine actual finished color. This product may injure plants and shrubs if it comes into contact with them during application. Cover plants with a drop cloth during application. Clear finished should not be applied over stain as it will seal the surface and prevent stain re-coating when necessary. Apply only when temperature is above 50°F.						
NOTE: Formulated without mercury or lead.								

Resin Type:	Alkyd
Solids:	Weight – 22.1% Average Volume – 18.2% Average
Weight Per Gallon:	6.90 lbs.
Viscosity:	12 – 15 seconds (#4 Ford Cup)
Specular Gloss:	0 – 3% @ 85 Degrees
Recommended Film Thickness:	Wet - Do not develop a film build.
VOC / VOS Statement:	This product contains less than 2.92 lbs. or 350 GPL per gallon.
Cautions:	<p>WARNING ! Keep Out of Reach of Children. Contains Petroleum Distillate. Harmful or fatal if swallowed. Do not use or store near heat or open flame.</p> <p>Use only in well-ventilated area. Do not breathe vapor or spray mist. Do not get in eyes, or on skin or clothing. Wear rubber gloves and protective clothing when applying or handling freshly treated lumber.</p> <p>FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flood with water several minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician.</p> <p>Environmental Hazards: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.</p> <p>Physical or Chemical Hazards: Combustible product. Do not use or store near heat or open flame</p> <p>Storage and Disposal: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.</p>