



**100% Acrylic Multi-Surface  
(AMS)  
Eggshell Finish 3601-01  
Semi-Gloss Finish 3603-01**

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
100% Acrylic	Eggshell or Semi-Gloss	Up to 350 Sq Ft Per Gallon	Brush, Roller, or Airless Spray	Clean Water	Warm Soapy Water	60 Minutes	4 Hours	30 Days
<b>PRODUCT NAME:</b> Acrylic Multi-Surface (AMS) Eggshell and Semi-Gloss		<p>Waterborne acrylic for interior and exterior use on marginally prepared metal or masonry surfaces. Features multiple sheens, fast dry, easy application.</p> <p>This product complies with LEED Green Building Rating System GS-11 for interior non-flat paints.</p>						
<b>WHERE TO USE:</b>		<p>Drywall</p> <p>Plaster</p> <p>Wood</p> <p>Metal</p> <ul style="list-style-type: none"> <li>• Self-priming directly to multiple surfaces</li> <li>• Excellent one-coat hide and stain blocking</li> <li>• Excellent adhesion to slick and glossy surfaces</li> <li>• Good exterior color and gloss retention</li> </ul>						
<b>Surface Preparation:</b>		<p><b>New Work:</b> The surface to be coated must be clean and free of contaminates.</p> <p><b>Repair Work:</b> On previously painted surfaces in good repair, no priming is generally necessary. On glossy surfaces remove the sheen with sandpaper or steel wool. Patch holes or cracks with appropriate filler. Spot prime bare areas with indicated primer. Remove any oil, chalk, dirt, wax or dust prior to re-coating. Any loose or flaking paint should be removed and the edges feather sanded to produce a smooth, uniform surface.</p>						
<b>Application:</b>		<p>Roller – 3/8" to 3/4" nap, depending on surface texture.</p> <p>Brush – Nylon or polyester filament.</p> <p>Spray – Tip size at atomization pressure will vary with type of equipment, viscosity and temperature. An orifice of .017 - .019 will provide the most satisfactory spray pattern.</p> <p>Apply only when surface and air temperatures are above 50°F.</p>						
<b>NOTE: Formulated without mercury or lead.</b>								

<b>Resin Type:</b>	100% Acrylic						
<b>Solids:</b>	<table border="1"> <thead> <tr> <th><b>3601-01 Eggshell</b></th> <th><b>3603-01 Semi-Gloss</b></th> </tr> </thead> <tbody> <tr> <td>Weight – 51.5%</td> <td>Weight – 52.6%</td> </tr> <tr> <td>Volume - 39.8%</td> <td>Volume - 38.9%</td> </tr> </tbody> </table>	<b>3601-01 Eggshell</b>	<b>3603-01 Semi-Gloss</b>	Weight – 51.5%	Weight – 52.6%	Volume - 39.8%	Volume - 38.9%
<b>3601-01 Eggshell</b>	<b>3603-01 Semi-Gloss</b>						
Weight – 51.5%	Weight – 52.6%						
Volume - 39.8%	Volume - 38.9%						
<b>Weight Per Gallon:</b>	10.6 lbs.						
<b>Viscosity:</b>	<table border="1"> <thead> <tr> <th><b>3601-01 Eggshell</b></th> <th><b>3603-01 Semi-Gloss</b></th> </tr> </thead> <tbody> <tr> <td>95 – 98 (Krebs Units)</td> <td>94 – 98 (Krebs Units)</td> </tr> </tbody> </table>	<b>3601-01 Eggshell</b>	<b>3603-01 Semi-Gloss</b>	95 – 98 (Krebs Units)	94 – 98 (Krebs Units)		
<b>3601-01 Eggshell</b>	<b>3603-01 Semi-Gloss</b>						
95 – 98 (Krebs Units)	94 – 98 (Krebs Units)						
<b>Specular Gloss:</b>	<table border="1"> <thead> <tr> <th><b>3601-01 Eggshell</b></th> <th><b>3603-01 Semi-Gloss</b></th> </tr> </thead> <tbody> <tr> <td>15 – 20% @ 85 degrees</td> <td>30 – 40% @ 60 degrees</td> </tr> </tbody> </table>	<b>3601-01 Eggshell</b>	<b>3603-01 Semi-Gloss</b>	15 – 20% @ 85 degrees	30 – 40% @ 60 degrees		
<b>3601-01 Eggshell</b>	<b>3603-01 Semi-Gloss</b>						
15 – 20% @ 85 degrees	30 – 40% @ 60 degrees						
<b>Recommended Film Thickness:</b>	Wet – 3.5 to 4.5 mils Dry – 1.4 to 1.8 mils						
<b>VOC / VOS Statement:</b>	These products contain less than 0.84 lbs. or 100 GPL per gallon.						
<b>Cautions:</b>	<p style="text-align: center;"><b>CAUTION !</b></p> <p style="text-align: center;">Do not take internally. Close container after each use.</p> <p style="text-align: center;"><b>KEEP OUT OF REACH OF CHILDREN.</b></p>						

08/2018

