



**Pro Prime Wallcovering
Primer / Sealer**
Microban® Built-In Protection
490
SECTION NO. 3 ADS-403

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
100% Acrylic	Flat	Up to 400-500 Sq Ft Per Gallon	Brush, Roller, Pad or Spray	Clean Water	Warm Soapy Water	1 Hour	2 Hours	7 Days
PRODUCT NAME: 490 PRO PRIME WALLCOVERING PRIMER/SEALER		Pro Prime Wallcovering Primer/Sealer is a premium, all-purpose, pigmented 100% Acrylic Primer/Sealer, which provides an ideal surface for wallcovering installation. Pro Prime Wallcovering Primer/Sealer can be used in most applications instead of oil based primers, and is easy to apply over a wide range of surfaces. The use of Pro Prime Wallcovering Primer/Sealer and a stripable adhesive, will provide stripability for fabric-backed vinyl wallcoverings. Pro Prime Wallcovering Primer/Sealer has excellent hiding power, dries white, and can be tinted with water based universal tint colors. This product contains Microban® protection that provides residual antimicrobial benefits engineered to last the useful life of the product. This is not a temporary treatment. It is introduced into the molecular structure of the paint film and will not wash out or wear off. This unique additive is EPA registered and will inhibit the growth of stain and odor causing bacteria, mold, mildew and other fungal growth on the dried paint film. Microban® protection does not take the place of normal cleaning and disinfecting procedures. For more information visit www.microban.com .						
WHERE TO USE:		New Bare Drywall On interior walls, such as living room kitchen or bathrooms. Plaster Paint Wood Paneling						
SURFACE PREPARATION:		Wall surface must be dry, clean, smooth, structurally sound, and free from grease, dirt and paste residue. Before proceeding with any unusual condition, consult your adhesive and wallcovering supplier. No sizing needed. Pro Prime Wallcovering Primer/Sealer will not block water- soluble stains. Check previously painted surfaces for bonding. Cracked and peeling paint must be removed before applying a primer.						
APPLICATION:		Stir product with a circular, lifting motion before you begin to paint. Pro Prime Wallcovering Primer/Sealer may be applied by brush, roller, pad or spray techniques at a rate of application not to exceed 400-500 square feet per gallon. For best results, apply a thin and even coat of Pro Prime Wallcovering Primer/Sealer. When brushing, use a quality, synthetic bristle brush. For roller application, use a ¼" nap roller on smooth surface. For spray application, Pro Prime Wallcovering Primer/Sealer should not be reduced. Test hang one strip before proceeding with the entire job. Wallcovering can be installed immediately after Pro Prime Wallcovering Primer/Sealer has dried. Normal drying time is one hour. Under high humidity conditions, allow drying time of 4 – 24 hours. Do not freeze. Use only when temperature is above 50°F. Cannot be diluted. Clean tools with water.						
NOTE: Formulated without mercury or lead.								

RESIN:	100% Acrylic
SOLIDS:	Weight – 43% Volume – 30%
WEIGHT PER GALLON:	9.77
VISCOSITY:	95 – 98 (Krebs Units)
SPECULAR GLOSS:	2% @ 60 Degrees
RECOMMENDED FILM THICKNESS:	Wet – 2 – 3 Mils Dry – .67 – 1 Mil
VOC – VOS STATEMENT:	This product contains less than 1.0 lbs or 120 GPL per gallon.
CAUTIONS:	DO NOT TAKE INTERNALLY ! CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN.

