

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: BLOCKFILLER
PRODUCT CODE: 529-11

HMS CODES: H F R P
1 0 0 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: O'Leary Paint Company
ADDRESS: 415 BAKER ST., LANSING, MI 48910
EMERGENCY PHONE: 800-424-9300 INFORMATION PHONE: (517) 482-0473
DATE REVISED : 05-13-01 NAME OF PREPARER : SCOTT BOWER
REASON REVISED : NEW PRODUCT

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
		OSHA PEL	ACGIH TLV	OTHER		

*** NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT ***

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING POINT: NA SPECIFIC GRAVITY (H2O=1): 1.5
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C. : 0.21 LB/GL (26 G/L)
SOLUBILITY IN WATER: INFINITE
APPEARANCE AND ODOR: WHITE OPAQUE LIQUID

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: NA METHOD USED: NA
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES

SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELFCONTAINED BREATHING APPARATUS. WATER SPRAY MAYBE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER SHOULD BE USED TO COOL CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DUE TO PRESSURE BUILD-UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE. DURING EMERGENCY CONDITIONS OVER-EXPOSURE MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE
CONDITIONS TO AVOID
KEEP FROM FREEZING

INCOMPATIBILITY (MATERIALS TO AVOID)
N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
N/A

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT; HEADACHES, NAUSEA AND DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
MAY CAUSE SKIN AND EYE IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
DRYING, ITCHING, CRACKING, BURNING, REDNESS AND SWELLING ARE ASSOCIATED WITH EXCESSIVE SKIN CONTACT.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITTING AND DIARRHEA.

HEALTH HAZARDS (ACUTE AND CHRONIC)
AVOID LONG TERM AND REPEATED CONTACT.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO
N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
N/A

EMERGENCY AND FIRST AID PROCEDURES
INHALATION: REMOVE TO FRESH AIR. EYES: IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES.
SKIN: REMOVE WITH SOAP AND WATER, REMOVE SOILED CLOTHING. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE, DO NOT INDUCE VOMITTING. CONSULT PHYSICIAN IMMEDIATELY. HAVE MATERIAL SAFETY DATA SHEET INFORMATION AVAILABLE.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

PROVIDE MAXIMUM VENTILATION. REMOVE ALL SOURCES OF IGNITION. TAKE UP SPILLED MATERIAL WITH SAWDUST, VERMICULITE OR OTHER ABSORBANT MATERIAL AND PLACE INTO CONTAINERS FOR PROPER DISPOSAL. WASH WITH WATER.

WASTE DISPOSAL METHOD

WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL ENVIRONMENTAL CONTROL REGULATION. EMPTY CONTAINERS SHOULD BE RECYCLED OR DISPOSED OF THROUGH AN APPROVED MANAGEMENT FACILITY.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BELOW 110°F. KEEP FROM FREEZING. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

OTHER PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

DO NOT BREATHE SPRAY MIST OR SANDING DUST. WHEN USED IN RESTRICTED VENTILATION AREAS WEAR NIOSH/MSHA APPROVED AIR SUPPLY RESPIRATOR OR HODD.

VENTILATION

USE WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAINMENT CONCENTRATION BELOW CURRENT APPLICABLE SAFETY STANDARDS IN APPLICATION AND CURING AREAS.

PROTECTIVE GLOVES

GLOVES CONSTRUCTED OF POLYVINYL ALCOHOL, NEOPRENE RUBBER OR LATEX RUBBER.

EYE PROTECTION

DO NOT GET IN EYES. SAFETY EYE WEAR WITH SPLASH GUARDS OR SIDESHIELD IS RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE USE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.

===== SECTION IX - DISCLAIMER =====

DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED BY O'LEARY PAINT CO. TO BE ACCURATE, BUT WE DO NOT ASSUME ANY LIABILITY FOR THE ACCURACY OF THIS INFORMATION. WE NEITHER SUGGEST NOR GUARANTEE THAT ANY HAZARD MENTIONED ARE THE ONLY ONES WHICH EXIST.