



**SUNGARD / FLAT**  
**Exterior Acrylic**  
**5550 LINE**  
*Formerly 2100 Line*

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
100% Acrylic	Flat	Up to 400 Sq Ft Per Gallon	Brush, Roller, Pad or Spray	Clean Water	Warm Soapy Water	60 Minutes	4 Hours	10-14 Days
<b>PRODUCT NAME:</b> 5550 LINE Sungard Exterior Acrylic Flat		A 100% Acrylic Latex Flat House Paint which provides lasting service over new or previously painted surfaces in good condition. Acrylic Latex House Paint will provide a durable and protective finish on any properly prepared and primed exterior surface. recommended for use on aluminum, vinyl, and wood siding, clapboard, shakes, shingles, plywood, masonry and primed metal down to surface and air temperature of 35 F.°						
<b>WHERE TO USE:</b>		Wood Hardboard Masonry Metal Galvanized  On exterior siding, foundations, facia, shutters or retaining walls.						
<b>Surface Preparation:</b>		Surface to be painted must be clean and free of dirt, chalk, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by power washing or hand scrubbing with an abrasive cleanser and water, followed by a clean water rinse. Wax should be removed by solvent cleaning. Grease and oil should be cleaned by using Coronado Sur-Prep I. Rust must be removed by blasting, hand sanding vigorously or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with the appropriate primer. <b>Priming – (New or Bare Surfaces)</b> WOOD – Use O’Leary Exterior Acrylic Primer 2090 or 560 Oil Primer MASONRY – Use Primer Sealer 43-10 or 48-11. To fill porous block, use 946-11 Latex Block Filler. FERROUS METAL – Rust Inhibiting Metal Primer such as 35-111, 2090, or 925-147 NON-FERROUS METAL – Use PermaBond 100-10 GALVANIZED – Use Acrylic Primer 36-111 or 100-10						
<b>Application:</b>		Stir product with a circular, lifting motion before you begin to paint. Acrylic Latex Flat House Paint may be applied by brush, spray, pad or roller, at a rate of application not to exceed 400 sq ft per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application, use a 3/8” or 1/2” nap cover for smooth surfaces, a 3/4” nap cover for semi-rough surfaces and a 1” or 1-1/4” nap cover for rough surfaces. For spray application, thin with clean water, up to 10% reduction if necessary. Do not apply to hot surfaces or in direct sunlight. Do not apply if rain is threatening.						
<b>NOTE: Formulated without mercury or lead.</b>								

<b>Resin Type:</b>	100% Acrylic
<b>Solids:</b>	Weight –48.1% Volume – 35.9%
<b>Weight Per Gallon:</b>	10.61 lbs.
<b>Viscosity:</b>	95 – 100 (Krebs Units)
<b>Specular Gloss:</b>	3 – 8% @ 85 Degrees
<b>Recommended Film Thickness:</b>	Wet – 3.0 to 4.0 mils Dry – 1.04 to 1.4 mils
<b>VOC – VOS Statement:</b>	This product contains less than 0.84 lbs or 100 GPL per gallon.
<b>CAUTIONS:</b>	<b>CAUTION !</b>  <b>Do not take internally. Close container after each use.</b>  <b>KEEP OUT OF REACH OF CHILDREN !</b>

Rev. 02/10/2021

